```
L3
    ANSWER 221 OF 379 CA COPYRIGHT 2004 ACS on STN
AN
    122:87754 CA
    Entered STN: 18 Feb 1995
ED
     Low-calcium cement for glass fiber reinforced cement
TI
     (GRC) products
IN
     Han, Ren; Hu, Guojun; Lou, Zonghan
     Zhejiang University, Peop. Rep. China
PΑ
     Faming Zhuanli Shenging Gongkai Shuomingshu, 7 pp.
SO
    CODEN: CNXXEV
DT
    Patent
    Chinese
LA
IC
    ICM C04B011-28
    ICS C04B022-08; C04B018-04
CC
   58-1 (Cement, Concrete, and Related Building Materials)
FAN.CNT 1
                                         APPLICATION NO. DATE
    PATENT NO.
                      KIND DATE
                                        APPLICATION NO.
                       ____
PI CN 1081426 A 19940202 CN 1993-105468 19930505
CN 1032686 B 19960904
PRAI CN 1993-105468 19930505
CLASS
 PATENT NO. CLASS PATENT FAMILY CLASSIFICATION CODES
 ______
 CN 1081426 ICM C04B011-28
               ICS C04B022-08; C04B018-04
    The low Ca cement comprises 50-62 wt.% aluminous cement
    clinkers and 38-50 wt.% gypsum. The cement may also contain
    <15% natural zeolite, limestone, slag, and/or coal ash
    and has fineness 250-400 m2/kg.. Preferably the cement has a
    chem. compn. of SiO2 1.2-8.1, Al2O3 25.3-37.5, CaO 29.5-49.0, and SO3
    13.0-24.0 wt.% and has a sp. surface area of 250-400 m2/kg.
    glass fiber reinforcing low calcium cement; aluminous low
    calcium cement gypsum
    Cement
      Slags
       (low-calcium cement from aluminous cement and
       gypsum for glass fiber reinforced cement products)
    Limestone, uses
    Zeolites, uses
    RL: NUU (Other use, unclassified); USES (Uses)
       (low-calcium cement from aluminous cement and
       qypsum for glass fiber reinforced cement products)
IT
    Ashes (residues)
       (coal, low-calcium cement from aluminous cement and
```

gypsum for glass fiber reinforced cement products)